



Product Code: EP1440H4 10-204

EcoPro G2 1350 Litre Upright Half Door Refrigerated Cabinet

---



## Features & Benefits

---

- Sleek, modern aesthetics, robust construction and market leading capacity. 'Smartphone style' fuzzy logic II touch sensitive control panel with high visibility temperature display
- Low energy refrigerant system with reduced running costs
- Improved internal fittings for easy cleaning
- Foster Circular II air distribution system maximises efficient operation even when shelves are fully loaded
- Operates efficiently in ambients up to 43°C
- Half door option designed to save energy
- Keep accessible products in the top section, bottom half can remain shut for longer preventing cold air loss.
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

## External Finish

<b>304 s/s</b>	Standard
<b>304 S/S back for island sitting</b>	Option

## Base Fittings

<b>Castors 80mm</b>	Standard
<b>Legs 150mm</b>	Option

## Electrical, Service & Ecodesign Data

<b>230/50/1</b>	Standard
<b>220/60/1 Electrical Supply</b>	Option
<b>Fuse Required</b>	13
<b>Global Warming Potential</b>	3
<b>Energy Efficiency Index</b>	63.89
<b>Refrigerant Charge</b>	0.140
<b>kWh (24 hours)</b>	3.84

## Internal Finish

<b>304 s/s</b>	Standard
----------------	----------

## Doors

<b>Half</b>	Standard
-------------	----------

## Product Extras

<b>Helicoil Mains Lead</b>	Option
----------------------------	--------

## Shelving

<b>Additional S/S Trayslides</b>	Option
<b>Additional GN2/1 Shelf</b>	Option

## Refrigeration

<b>R290 - Energy Efficient</b>	Standard
<b>Integral Refrigeration System</b>	Standard
<b>Less Condensing Unit</b>	Option
<b>Remote Refrigeration System</b>	Option

## Specification

<b>Dimensions (Width)</b>	1440
<b>Dimensions (Height)</b>	2080
<b>Dimensions (Depth)</b>	820
<b>Weight (Unpacked, kg)</b>	182.5
<b>Weight (Packed, kg)</b>	199.1
<b>Gross Volume</b>	1350
<b>Noise DbA @ 1M</b>	69.8

## Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care