



# Product Code: EP1/2L 43-108

## Freezer two door counter

---



The versatile Foster EcoPro G3 counter range offers a huge selection of models, build options and accessories to ensure you find the perfect storage solution for your business.

## Features & Benefits

---

- A reduced footprint– the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer - all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Supplied with helicoil mains lead, allowing easy movement for cleaning purposes
- Operates efficiently in ambient temperatures of up to 43°C

## Shelving

<b>4 shelves (GN1/1)</b>	Standard
<b>Gastronorm Pans</b>	Option
<b>Additional S/S Trayslides</b>	Option
<b>Additional GN1/1 Shelf</b>	Option

## Refrigeration

<b>R290 - Energy Efficient</b>	Standard
<b>Integral Refrigeration System</b>	Standard
<b>Remote Refrigeration System</b>	Option
<b>RH Mounted Ref Unit</b>	Option

## Specification

<b>Gross volume (ltrs)</b>	280
<b>Freezer -18/-21°C</b>	Standard
<b>Width (mm)</b>	1365
<b>Depth (mm)</b>	700
<b>Height (mm)</b>	865
<b>Worktop</b>	Standard

## Base Fittings

<b>Castors 80mm</b>	Standard
<b>100mm legs in lieu of castors</b>	Option

## Electrical & Service Data

<b>230/50/1</b>	Standard
<b>Fuse Required (A)</b>	10

## Finish

<b>304 s/s ext &amp; int</b>	Standard
<b>304 S/S back for island sitting</b>	Option

## Doors

<b>Solid</b>	Standard
--------------	----------

## Product Extras

<b>Helicoil Mains Lead</b>	Option
<b>Less Worktop</b>	Option
<b>Splashback</b>	Option
<b>304 S/S Back and Unit Cover</b>	Option


## Energy

<b>kWh (24 hours)</b>	7.02
<b>AEC</b>	2561
<b>Nett Volume</b>	172.3
<b>Energy Grade</b>	E
<b>Global Warming Potential</b>	3
<b>Energy Efficiency Index</b>	75.63

## Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm

# Energy Performance Data and information



## Application


This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.