

## **CRNF2130**

Freezer Room

## **Product Features**

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- · Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access

Design and Material		
Door Number & Type		1 hinged solid door W:700 H:1765
Max Load on Floor	kg/m²	2000
Exterior Finish		White
Interior Finish		White
Interior Light		LED
Lock		Yes

Measures		
Internal Volume	m³	10.06
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	760 / 730
Gross / Net Volume	1	
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	200
Termometer		Yes
Power and Consumptio	n	
Power and Consumption  Energy Consumption	n kWh/24h	31.78
		31.78 11598
Energy Consumption	kWh/24h	
Energy Consumption Annual Energy Consumption	kWh/24h	11598
Energy Consumption Annual Energy Consumption Power	kWh/24h	11598 13 Amp
Energy Consumption Annual Energy Consumption Power Max Ambient	kWh/24h kWh/year	11598 13 Amp 40°C at 40% RH
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power	kWh/24h kWh/year	11598 13 Amp 40°C at 40% RH 1630
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency	kWh/24h kWh/year W V/Hz dB(A)	11598 13 Amp 40°C at 40% RH 1630 220-240/50
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level	kWh/24h kWh/year W V/Hz dB(A)	11598 13 Amp 40°C at 40% RH 1630 220-240/50
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Weight and Dimensions	kWh/24h kWh/year W V/Hz dB(A)	11598 13 Amp 40°C at 40% RH 1630 220-240/50 60
Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Weight and Dimensions Internal Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A)	11598 13 Amp 40°C at 40% RH 1630 220-240/50 60 1860 x 2760 x 1960





Strong handle

Shelf as accessory