

CRPF1518

Chiller Room

Product Features

- Plug-In - ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Design and Material

| | | |
|--------------------|----------------------------------|------|
| Door Number & Type | 1 hinged solid door W:700 H:1845 | |
| Max Load on Floor | kg/m ² | 1500 |
| Exterior Finish | White | |
| Interior Finish | White | |
| Interior Light | LED | |
| Lock | Yes | |

Measures

| | | |
|--------------------|-------------------|-----------|
| Internal Volume | m ³ | 4.48 |
| Wall Thickness | mm | 80 |
| Insulation Density | kg/m ³ | 42 |
| Temperature Range | °C | 0 to +8 |
| Climate Class | 5 | |
| Gross / Net Weight | kg | 304 / 284 |
| Gross / Net Volume | l | |

Cooling and Functions

| | | |
|--------------------|--------------------|-----|
| Type of Controller | Electronic | |
| Type of Cooling | Ventilated | |
| Type of Defrost | Automatic, hot gas | |
| Refrigerant | R290 | |
| Refrigerant Charge | g | 130 |
| Thermometer | Yes | |

Power and Consumption


| | | |
|---------------------------|----------------|------------|
| Energy Consumption | kWh/24h | 17.93 |
| Annual Energy Consumption | kWh/year | 6545 |
| Power | 13 Amp | |
| Max Ambient | 40°C at 40% RH | |
| Input Power | W | 830 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |

Weight and Dimensions

| | | |
|----------------------------|-----|--------------------|
| Internal Dimension (WxDxH) | mm | 1340 x 1640 x 2040 |
| External Dimension (WxDxH) | mm | 1500 x 1800 x 2200 |
| Packed Dimension (WxDxH) | mm | 2200 x 1300 x 2400 |
| 40ft Container Load | pcs | 14 |



Strong handle



Shelf as accessory