



## **CRPF1524**

## Chiller Room

## **Product Features**

## • Plug-In - ready after assembly

- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

Design and Material		
Door Number & Type		1 hinged solid door W:700 H:1845
Max Load on Floor	kg/m²	1500
Exterior Finish		White
Interior Finish		White
Interior Light		LED
Lock		Yes

Measures			
Internal Volume	m³	6.12	
Wall Thickness	mm	80	
Insulation Density	kg/m³	42	
Temperature Range	°C	0 to +8	
Climate Class		5	
Gross / Net Weight	kg	326 / 296	
Gross / Net Volume	1		
Cooling and Functions	-		
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic, hot gas	
Refrigerant		R290	
Refrigerant Charge	g	130	
Termometer		Yes	
Power and Consumption			
Energy Consumption	kWh/24h	18.72	
Annual Energy Consumption	kWh/year	6833	
Power		13 Amp	
Max Ambient		40°C at 40% RH	
Input Power	W	860	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	60	
Weight and Dimensions			
Internal Dimension (WxDxH)	mm	1340 x 2240 x 2040	
External Dimension (WxDxH)	mm	1500 x 2400 x 2200	
Packed Dimension (WxDxH)	mm	2200 x 1600 x 2400	
40ft Container Load	pcs	12	





Strong handle

Shelf as accessory