





CRPF2121

Chiller Room

Product Features

Plug-In - ready after assembly

- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access

| Design and Material | | |
|---------------------|----------------------------------|-------|
| Door Number & Type | 1 hinged solid door W:700 H:1845 | |
| Max Load on Floor | kg/m² | 1500 |
| Exterior Finish | | White |
| Interior Finish | | White |
| Interior Light | | LED |
| Lock | | Yes |

| Measures | | |
|----------------------------|----------|--------------------|
| Internal Volume | m³ | 7.68 |
| Wall Thickness | mm | 80 |
| Insulation Density | kg/m³ | 42 |
| Temperature Range | °C | 0 to +8 |
| Climate Class | | 5 |
| Gross / Net Weight | kg | 488 / 458 |
| Gross / Net Volume | 1 | |
| Cooling and Functions | | |
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 150 |
| Termometer | | Yes |
| Power and Consumptio | n | |
| Energy Consumption | kWh/24h | 21.12 |
| Annual Energy Consumption | kWh/year | 7709 |
| Power | | 13 Amp |
| Max Ambient | | 40°C at 40% RH |
| Input Power | W | 905 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 60 |
| Weight and Dimensions | ; | |
| Internal Dimension (WxDxH) | mm | 1940 x 1940 x 2040 |
| External Dimension (WxDxH) | mm | 2100 x 2100 x 2200 |
| Packed Dimension (WxDxH) | mm | 2200 x 1600 x 2400 |
| | | |





Strong handle

Shelf as accessory