

Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



Modular Cooking Range Line

700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres

371099 (E7PCEH2KF0)

24,5+24,5-It electric pasta cooker with 2 wells

Short Form Specification

Item No.

Infrared heating system positioned below the well. Constant starch removal during the cooking process. Pressed tank in 316 AISI stainless steel to protect against corrosion. Manual water tap. Height adjustable feet in stainless steel. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Unit to have infrared heating system positioned beneath the base of the wells.
- Water basins in 316 type Stainless steel.
- Water basins are seamlessly welded into the top of the appliance.
- Provided with integrated drip tray on which baskets can be placed for draining purposes.
- 24.5 liters water basins.
- Unit to feature skimming zone for starch removal: improved water quality over time.
- Easy-to-use control panel.
- Safety thermostat to avoid operation without water.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.
- EnergyControl: unique feature for fine power adjustment to control boiling level and optimize energy consumption.
- Automatic lifting system (optional accessory): 200mm wide unit with two stainless steel basket supports, holding one GN 1/2 basket each, to be placed on either or both sides of machine to provide automatic lifting for four small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- All major compartments located in front of unit for ease of maintenance.
- IPX4 water resistance certification.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL:



Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres

Included Accessories

• 2 of Door for open base cupboard PNC 206350

Optional Accessories

- 4 wheels, 2 swivelling with brake (700/900XP). PNC 206135 ☐
 It is mandatory to install with base supports for feet/wheels.
- Flanged feet kit
 PNC 206136 □
 Frontal kicking strip for concrete installation, 200mm
- Frontal kicking strip for concrete installation, 400mm

 PNC 206147 □
- Frontal kicking strip for concrete installation, 800mm

 PNC 206148 □
- Frontal kicking strip for concrete installation, 1000mm
 PNC 206150 □
- Frontal kicking strip for concrete installation, 1200mm

 PNC 206151 □
- Frontal kicking strip for concrete installation, 1600mm
 PNC 206152 □
- Frontal kicking strip, 200mm (not for refrfreezer base)

 PNC 206174 □
- Frontal kicking strip, 400mm (not for refrfreezer base)

 PNC 206175 □
- Frontal kicking strip, 800mm (not for refrfreezer base)
 PNC 206176 □
- Frontal kicking strip, 1000mm (not for refrfreezer base)

 PNC 206177 □
- Frontal kicking strip, 1200mm (not for refrfreezer base)

 PNC 206178 □
- Frontal kicking strip, 1600mm (not for refrfreezer base)

 PNC 206179 □
- 4 feet for concrete installation PNC 206210 □
- Pair of side kicking strips
 Pair of side kicking strips for concrete
 PNC 206249 □
 PNC 206265 □
- installation

 Water coulumn with swivel arm (water column PNC 206289 □ extension not included)
- extension not included)

 Water column extension for 700 line

 PNC 206291 □

 Chiana variant 200 mm.
- Chimney upstand, 800mm
 Right and left side handrails
 PNC 206307 □
- Energy saving device for pasta cookers
 PNC 206344 □
 PNC 206350 □
- Automatic programmable basket lifting system
 PNC 206350 □
- for 24,5lt pasta cookers, 2 lifters

 Base support for feet or wheels 400mm (700/900XP)

 PNC 206366 □
- Base support for feet or wheels 800mm PNC 206367 ☐ (700/900)
- Base support for feet or wheels 1200mm PNC 206368 □
- (700/900)

 Base support for feet or wheels 1600mm PNC 206369 □
- (700/900)

 Base support for feet or wheels 2000mm PNC 206370 □
- (700/900)

 Poor papeling 900mm (700/000)

 Poor papeling 900mm (700/000)
- Rear paneling 800mm (700/900) PNC 206374 □
- Rear paneling 1000mm (700/900)
 Rear paneling 1200mm (700/900)
 PNC 206375 □
 PNC 206376 □
- 6 baskets (105x105) for pasta cookers 700XP PNC 206397 □
- Chimney grid net, 400mm PNC 206400 □
- 2 side covering panels, h=700mm, d=700mm
 Frontal handrail 800mm
 PNC 216000 □
 PNC 216047 □


•	Frontal handrail 1200mm	PNC	216	049	
•	Frontal handrail 1600mm	PNC	216	050	
•	Large handrail - portioning shelf, 400mm	PNC	216	185	
•	Large handrail - portioning shelf, 800mm	PNC	216	186	
•	Support frame for 4 baskets for 24,5lt pasta cookers	PNC	921	606	
•	Lid for 24,5lt pasta cookers	PNC	921	607	
•	2 half size baskets 170x220 for 24,5lt pasta cookers	PNC	921	610	
•	Full size basket for 24,5lt pasta cookers	PNC	921	611	
•	4 baskets 105x160 for 24,5lt pasta cookers (921606 must be ordered together)	PNC	921	618	
•	2 half size baskets 105x350 for pasta cookers for 24,5lt pasta cookers	PNC	921	619	



Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres



Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres




31 1/2 "
800 mm

D = Drain

EI = Electrical connection

WI = Water inlet





Supply voltage:

371099 (E7PCEH2KF0) 400 V/3N ph/50/60 Hz

Connected load: 12 kW Total Watts: 12 kW

Water

Drain "D": 1"
Incoming Cold Water line size: 1/2"
Total hardness: 5-50 ppm

Electrolux recommends the use of treated water, based on

testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Key Information

Usable well dimensions (width): 250 mm Usable well dimensions (height): 300 mm Usable well dimensions (depth): 400 mm Well Capacity (MAX): 24.5 It MAX Net weight: 50 kg Shipping weight: 105 kg Shipping height: 1140 mm Shipping width: 880 mm Shipping depth: 830 mm Shipping volume: 0.83 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

