



Product Code: EP1/2H 12-146

EcoPro G2 1/2 Refrigerated Counter with Drawers  
(door/drawer combination: 2-2)

---



## Features & Benefits

---

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Drawers will accommodate GN1/1 pans to a max depth of 150mm

## External Finish

<b>304 s/s</b>	Standard
<b>304 S/S back for island sitting</b>	Option
<b>Worktop</b>	Standard

## Base Fittings

<b>100mm legs in lieu of castors</b>	Option
<b>Castors 80mm</b>	Standard
<b>Legs 150mm</b>	Option

## Electrical, Service & Ecodesign Data

<b>230/50/1</b>	Standard
<b>Fuse Required</b>	13
<b>Global Warming Potential</b>	3
<b>Energy Efficiency Index</b>	19.00
<b>Refrigerant Charge</b>	0.15
<b>kWh (24 hours)</b>	1.08

## Internal Finish

<b>304 s/s</b>	Standard
----------------	----------

## Doors

<b>Half Door / Half Door</b>	Standard
------------------------------	----------

## Product Extras

<b>Helicoil Mains Lead</b>	Option
<b>Less Worktop</b>	Option

## Shelving

<b>Additional S/S Trayslides</b>	Option
----------------------------------	--------

## Refrigeration

<b>R290 - Energy Efficient</b>	Standard
<b>Integral Refrigeration System</b>	Standard
<b>Less Condensing Unit</b>	Option
<b>Remote Refrigeration System</b>	Option
<b>RH Mounted Ref Unit</b>	Option

## Specification

<b>Dimensions (Width)</b>	1415
<b>Dimensions (Height)</b>	865
<b>Dimensions (Depth)</b>	700
<b>Gross Volume</b>	280
<b>Noise DbA @ 1M</b>	65.2

## Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm
- Any mix of two or three drawer units is possible, as is any combination of drawers and doors. Important - drawer sections are supplied without shelves. Will accommodate pans (optional extra): 1/2 drawers up to 150mm, 1/3 drawers up to 100mm (top drawer max. 70mm on 1/3 drawers)



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care