



Product Code: EP2/3H 12-402

EcoPro G2 Refrigerated Counter with Drawers
(door/drawer combination: D-D-2)



Features & Benefits

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Drawers will accommodate GN1/1 pans to a max depth of 150mm

External Finish

| | |
|---------------------------------|----------|
| 304 s/s | Standard |
| 304 S/S back for island sitting | Option |
| Worktop | Standard |

Base Fittings

| | |
|-------------------------------|----------|
| 100mm legs in lieu of castors | Option |
| Castors 80mm | Standard |
| Legs 150mm | Option |

Electrical, Service & Ecodesign Data

| | |
|--------------------------|----------|
| 230/50/1 | Standard |
| Fuse Required | 13 |
| Global Warming Potential | 3 |
| Energy Efficiency Index | 33.21 |
| Refrigerant Charge | 0.150 |
| kWh (24 hours) | 2.70 |

Internal Finish

| | |
|---------|----------|
| 304 s/s | Standard |
|---------|----------|

Doors

| | |
|-------------------------------------|----------|
| Solid Door / Solid Door / Half Door | Standard |
|-------------------------------------|----------|

Product Extras

| | |
|---------------------|--------|
| Helicoil Mains Lead | Option |
| Less Worktop | Option |

Shelving

| | |
|---------------------------|--------|
| Gastronorm Pans | Option |
| Additional S/S Trayslides | Option |
| Additional GN2/1 Shelf | Option |

Refrigeration

| | |
|-------------------------------|----------|
| R290 - Energy Efficient | Standard |
| Integral Refrigeration System | Standard |
| RH Mounted Ref Unit | Option |

Specification

| | |
|---------------------|------|
| Dimensions (Width) | 2480 |
| Dimensions (Height) | 865 |
| Dimensions (Depth) | 800 |
| Gross Volume | 760 |
| Noise DbA @ 1M | TBC |

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm
- Any mix of two or three drawer units is possible, as is any combination of drawers and doors. Important - drawer sections are supplied without shelves. Will accommodate pans (optional extra): 1/2 drawers up to 150mm, 1/3 drawers up to 100mm (top drawer max. 70mm on 1/3 drawers)



Application

This appliance is intended for use in ambient temperatures up to 40°C

Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care