



Product Code: EP2/3H 12-414

EcoPro G2 Refrigerated Counter with Drawers  
(door/drawer combination: D-D-3)

---



## Features & Benefits

---

- High Quality 304 Stainless Steel Exterior Build Quality
- ECA Scheme Approved - as ECA products are guaranteed to be energy efficient, money can be claimed back on your investment
- Smartphone style' touch sensitive hidden until lit control pannel
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- Energy-saving Hydrocarbon refrigerant option at no extra cost
- High performance cyclopentane foam
- Airlines' ventilation system reduces compressor running time by 15%
- Take the travel out of food preparation
- Drawers will accommodate GN1/1 pans to a max depth of 150mm

## External Finish

304 s/s	Standard
304 S/S back for island sitting	Option
Worktop	Standard

## Base Fittings

100mm legs in lieu of castors	Option
Castors 80mm	Standard
Legs 150mm	Option

## Electrical, Service & Ecodesign Data

230/50/1	Standard
Fuse Required	13
Global Warming Potential	3
Energy Efficiency Index	33.31
Refrigerant Charge	0.150
kWh (24 hours)	2.70

## Internal Finish

304 s/s	Standard
---------	----------

## Doors

Solid Door / Solid Door / Third Door	Standard
--------------------------------------	----------

## Product Extras

Helicoil Mains Lead	Option
Less Worktop	Option

## Shelving

Gastronorm Pans	Option
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option

## Refrigeration

R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
RH Mounted Ref Unit	Option

## Specification

Dimensions (Width)	2480
Dimensions (Height)	865
Dimensions (Depth)	800
Gross Volume	760
Noise DbA @ 1M	TBC

## Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Depth with door open is 1113mm
- Decibel rating measured 1m high from the floor and 1m out from the counter
- 60Hz model supplied as 220v machine with separate transformer for conversion to 115v supply.
- Adequate airflow must be kept around the counter: 150mm
- Any mix of two or three drawer units is possible, as is any combination of drawers and doors. Important - drawer sections are supplied without shelves. Will accommodate pans (optional extra): 1/2 drawers up to 150mm, 1/3 drawers up to 100mm (top drawer max. 70mm on 1/3 drawers)



## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



Energy



Quality



Value



Design



Hygiene



After Care