Temperature Range	+2/+10°C	T	illere.		1111
Refrigerant	R134a				1111
Type of Defrost	Off Cycle			6	
Exterior Finish	Stainless Steel		and the second second	and the second se	•
Interior Finish	Stainless Steel		ES	SL900	
Power Required	13 Amp				
Max Ambient	30°C at 55% RH				
Climate Class	4			Cabinet suppli castors and fee Diagram shows with feet, cast 40mm to	t fitted. s height ors add
		h man	NULL	7	
F	F				


## Gastronorm Counter **ESL Range**

## Features and Benefits

- Fully automatic .
- Wet wall with fan assisted cooling
- Adjustable shelves •
- Fitted with castors and adjustable • feet. Removing castors will lower unit by 40mm
- Digital controller and temperature • display
- Self closing doors .
- Replaceable door gasket •
- Accepts Gastronorm pans (not . supplied)
- 1/1 Gastronorm cupboards







	Model	Description		Dime н	nsions w	(mm)	Kg	Gross Int. Volume	Net Useable Vol.	kWh/ Annum	No. of Shelves	Price	Energy Rating	Next Day
E	ESL900		Ext.	920	900	700	72	300ltr	169ltr	940	1 Per	£850	C	<i>√</i>
	LOLSOU		Int.	500	830	595		(10.59 cu.ft)			door			
	ESL1365 Stainless Steel	Ext.	920	1365	700	90	380ltr	254ltr	1350	1 Per	01 105			
	ESC 1305	Stall liess Steel	Int.	500	1295	595	90	(13.41 cu.ft)	20410	1330	door	£1,195		V