



SLICER GSM-300 230/50/1 UK

Ø 300 mm blade.



5051075



SPECIFICATIONS

Blade diameter: 300 mm
Cutting capacity: 210 mm x 220 mm
Slice thickness: 0 mm - 16 mm
Carriage run: 260 mm
Total loading: 246 W
IP Protection grade: X1
Electrical supply: 230 V / 50 Hz / 1~
Plug: UK

External dimensions (W x D x H)

- ✓ Width: 700 mm
 - ✓ Depth: 500 mm
 - ✓ Height: 490 mm
- Net weight: 20.7 kg
Crated dimensions
485 x 630 x 530 mm
Gross weight: 25 kg

SALES DESCRIPTION

Belt driven slicer.

- ✓ Slicer made of a special anodized aluminum alloy, hygienic, and anticorrosive.
- ✓ Professional slicer with blade protective ring and carriage lock.
- ✓ High-powered ventilated motor.
- ✓ Easy-to-mount sharpener.
- ✓ Decimal thickness adjustment from 0 to 16 mm.
- ✓ Plate mounted on self-lubricating bushings and bearings.
- ✓ Easy cleaning, no need for tools. Dishwasher-safe detachable grip points.
- ✓ Luminous double on/off 24V switch.
- ✓ Safety print.

INCLUDES

- ✓ Blade removal tool.



www.sammic.co.uk
Food Service Equipment Manufacturer
Unit 2, Trevanth Road
Troon Industrial Park
LE4 9LS - Leicester
uksales@sammic.com
Tel.: +44 0116 246 1900



Project	Date
Item	Qty
Approved	

DYNAMIC PREPARATION
COMMERCIAL SLICERS

product sheet
updated 29/01/2025