

REFRIGERATOR COMPACT K420R C DR G U

Product series: Compact
Item number: 151422030

The HOSHIZAKI COMPACT K420R C DR G U is a REFRIGERATOR on castors with a net usable volume of 265 Ltr.

The COMPACT series offers a rare combination: These cabinets are food-safe, space-saving, and come with excellent energy ratings for their class. With a footprint of only 59.5 x 66.7 cm, these small space storage cabinets are easy to fit in, especially when space is limited. These specifications make the series such a popular choice for those operators who do not require heavy-duty Gastronorm equipment.



Food Safety

Thanks to the Hoshizaki air distribution system, temperatures are correct and uniform throughout the entire cold room, ensuring perfectly food-safe temperatures at all times

Low-Running Energy Costs

The Energy Efficiency Class of the COMPACT K420R C DR G U is B. The COMPACT series offers a range of extremely energy-efficient refrigeration units for small spaces.

Comfortable Work Environment

Contributes to a healthier work environment with low noise levels 39.8 dB(A), when the compressor is running. Low heat emission due to short compressor running times.

Hygiene & Ergonomic Design

The COMPACT series features several design extras, implemented to simplify daily cleaning routines. One of the features for optimized operator safety is the full-height integrated handles.

The COMPACT K420R C DR G U comes with:

- Refrigerant: The REFRIGERATOR uses HC refrigerant R600a
- Air circulation system
- Right-hand hinged door
- Integrated full-height door handle
- Internal LED light
- Reversible door
- Door lock for extra security
- White shelves
- Automatic defrost with re-evaporation of defrost water

SPECIFICATIONS

Product title	REFRIGERATOR	Energy Consumption (kWh/Year)	310
Temperature Range	+1/+12°C	Energy Efficiency Class Standard	ISO 22041-2019
Volume, Gross (ltr.)	343	Energy Efficiency Class	B
Net Usable Volume (ltr.)	265	Energy Efficiency Index EEI	29.62
Exterior	Stainless	Sound Level – dB(A)	39.8
Interior	White Finish	Climate Class	4 (max. ambient temp. of 30 °C with 55% RH)
Dimensions W x D x H (mm)	595 x 642 x 1901	Legs / Castors	H = 125 mm (C2)
Weight, Packed (kg)	87	Refrigerant (kg)	0.048
Insulation (mm)	52 (polyurethane)	CO2 equivalent (kg)	0.144
Refrigerant	R600a	GN or Tray Size (mm)	Shelf 483.8 x 433 mm
GWP	3	Maximum number of shelves	26
Ref. capacity at -10°C (Watt)	122	Number of shelves	5
Power Supply	230V, 50 Hz	Equipped with	Right hand hinged reversible door with lock, 5 white shelves, bottom shelf 484.7 (W) x 300 (D) mm. Exterior: Stainless. Interior: PS lining in white
Connection Load (Watt)	120	Door Type	Insulated Door