



## 3-SECTION REFRIGERATED COUNTER, HC SCR-180DG-LRR-RRC-C1 U

Product series: [Snowflake GII](#)

Item number: [879020861](#)

The [Snowflake GII series](#) is brought to you by Japanese and Danish engineering excellence, dedicated to simplifying the day-to-day work routines of kitchen staffs all around the world.

The technology behind the performance boost of Snowflake GII is the [tropicalised cooling system](#) enduring up to +40°C. Additionally, the cooling agent of the new generation of Snowflake is the [eco-friendly refrigerant R290](#), a natural gas (HC) that enhances the performance and cuts down energy consumption significantly.

Both interior and exterior are built of anti-corrosion stainless steel, which is among the best choices for hygienic and food safe cooking environments.

The [Snowflake GII SCR-180DG-LRR-RRC-C1 U](#) is a 3-section refrigerated counter with a net internal volume of 257 Ltr.

As a product that is designed and built to last, this refrigerated counter combines an innovative design concept, premium materials and clever extras:

- [Minimum cool air lost](#): double insulated and extra wide door gaskets help to keep the cold air into the cabinet
- Both interior and exterior are built of stainless steel which is among the best choices for hygienic and food safe cooking environments
- [Anti-tilt mechanism](#): extra-long drawers with u-shaped, telescopic rails
- Multiple door-drawer combinations possible
- Removable gaskets make sure you can clean the device thoroughly
- This and other thoughtful extras, such as the [cleaning-free condenser](#), are designed to reduce kitchen cleaning times whilst storing foods protectively in the best possible way

[The refrigerant used in all Snowflake GII HC models is R290.](#)

This agent is a natural gas which enhances the performance of the refrigerated counter and has, compared to other refrigerants, a minimal ozone depletion potential.

### SPECIFICATIONS

Product title	3-Section Refrigerated Counter, HC
Temperature range	-2/+8°C
Internal volume gross (l)	500
Net usable volume (l)	257
CO2 equivalent (kg)	0.237
Net weight (kg)	117
Gross Weight Packed (kg)	141
Climate class	5
Energy label	C

Interior	Stainless steel
Exterior	Stainless steel
Number of shelves	6
Energy Consumption (kWh/24hrs) at 32.2°C ambient and 65% RH	927
Electric connection Load (kW)	0.19
Electric connection	230V, 1N-/50 Hz
Outside Dimensions W x D x H (mm)	1780 x 700 x 830-900 (with legs)
Refrigerant	R290