





SOCA25090A

Serve Over Counter

Product Features

- Excellent product visibility
- 900 mm deep stainless steel deck
- · Anti mist front glass
- · Glass front lifts up for easy cleaning
- · Stainless steel rear shelf
- · Ventilated cooling
- Temperature Class 3M1
- · LED top light
- Stainless steel bumper bars
- 2 x 220V sockets to rear
- Can be multiplexed with kit (POA)

Premium serve over counter display with 900 mm deck

Discover our high-quality serve over counter, perfect for your deli or butcher shop. This premium counter is designed to impress with its anti-mist glass, LED lighting, and a stainless-steel deck that extends 900mm deep. The rear airholes and ventilated cooling system ensure that your meats, cheeses, and prepared meals remain perfectly chilled. Enjoy the convenience of easy cleaning with a lift-up front glass that securely stays in place and a stainless steel interior. Not only does it provide ample under-storage with wide doors accommodating E2 boxes, but our SOC range also offers the flexibility to multiplex and create a comprehensive counter solution. Enhance your counter with optional extras such as shelves, knife blocks, mobile plexiglass dividers, two-tier GNpan holders, and a red light specifically designed for butchers. For specific requirements and temperatures, we offer custom orders from our factory. Reach out to our dedicated sales team for further assistance and guidance.

Measures and Content		
Total Display Area	m²	2.29
Temperature Range	°C	0 to +4
Climate Class		3
Gross / Net Weight	kg	410 / 325
Gross / Net Volume	I	654
Design and Material		
Door Number & Type		
Tempered glass		Yes
Shelves Number & Type		
Feet / Legs		Adjustable Feet
Exterior Finish		
Interior Finish		Stainless Steel
Interior Light		LED
Lock		No
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic-Electric
Refrigerant		R290
Refrigerant Charge	g	2 x 150
Thermometer		Yes
Power and Consumption		
Energy Class		F
Energy Consumption	kWh/24h	10
Annual Energy Consumption	kWh/year	3650
Power		13 Amp
Input Power	W	690
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	59
Dimensions		
Internal Dimension (WxDxH)	mm	2500 x 900 x
External Dimension (WxDxH)	mm	2548 x 1120 x 1190
Packed Dimension (WxDxH)	mm	2750 x 1250 x 1400
40ft Container Load	pcs	4