



SOCA37590A

Serve Over Counter

Product Features

- Excellent product visibility
- 900 mm deep stainless steel deck
- Anti mist front glass
- Glass front lifts up for easy cleaning
- Stainless steel rear shelf
- Ventilated cooling
- Temperature Class 3M1
- LED top light
- Stainless steel bumper bars
- 2 x 220V sockets to rear
- Can be multiplexed with kit (POA)

Premium serve over counter display with 900 mm deck

Discover our high-quality serve over counter, perfect for your deli or butcher shop. This premium counter is designed to impress with its anti-mist glass, LED lighting, and a stainless-steel deck that extends 900mm deep. The rear airholes and ventilated cooling system ensure that your meats, cheeses, and prepared meals remain perfectly chilled. Enjoy the convenience of easy cleaning with a lift-up front glass that securely stays in place and a stainless steel interior. Not only does it provide ample under-storage with wide doors accommodating E2 boxes, but our SOC range also offers the flexibility to multiplex and create a comprehensive counter solution. Enhance your counter with optional extras such as shelves, knife blocks, mobile plexiglass dividers, two-tier GN-pan holders, and a red light specifically designed for butchers. For specific requirements and temperatures, we offer custom orders from our factory. Reach out to our dedicated sales team for further assistance and guidance.

Measures and Content

Total Display Area	m ²	3.31
Temperature Range	°C	0 to +4
Climate Class		3
Gross / Net Weight	kg	565 / 470
Gross / Net Volume	l	982

Design and Material

Door Number & Type	
Tempered glass	Yes
Shelves Number & Type	
Feet / Legs	Adjustable Feet
Exterior Finish	
Interior Finish	Stainless Steel
Interior Light	LED
Lock	No

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic-Electric	
Refrigerant	R290	
Refrigerant Charge	g	2 x 150
Thermometer	Yes	

Power and Consumption

Energy Class		F
Energy Consumption	kWh/24h	14.4
Annual Energy Consumption	kWh/year	5256
Power		13 Amp
Input Power	W	1000
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	59

Dimensions

Internal Dimension (WxDxH)	mm	3750 x 900 x
External Dimension (WxDxH)	mm	3798 x 1120 x 1190
Packed Dimension (WxDxH)	mm	4000 x 1250 x 1400
40ft Container Load	pcs	3

